



## Stock sizes

Type	Nom. delivery size			Weight kg/m	Guaranteed finished size, mm				
	OD mm	wall mm	ID mm		outer chocking OD	ID	inner chocking OD	ID	
<b>3020</b>	30.7	6.10	18.5	3.70	30.0	20.0	29.20	19.20	CW
<b>3525</b>	35.7	6.10	23.5	4.47	35.0	25.0	34.20	24.20	CW
<b>4020</b>	40.7	11.15	18.4	8.15	40.0	20.0	39.10	19.10	CW
<b>4030</b>	40.7	6.10	28.5	5.22	40.0	30.0	39.20	29.20	CW
<b>4525</b>	45.7	11.15	23.4	9.53	45.0	25.0	44.10	24.10	CW
<b>4530</b>	45.7	8.65	28.4	7.92	45.0	30.0	44.10	29.20	CW
<b>4535</b>	45.7	6.10	33.5	5.97	45.0	35.0	44.20	34.20	CW
<b>5025</b>	50.7	13.65	23.4	12.51	50.0	25.0	49.10	24.10	CW
<b>5030</b>	50.7	11.15	28.4	10.90	50.0	30.0	49.10	29.10	CW
<b>5035</b>	51.4	9.55	32.3	9.86	50.0	35.0	48.80	34.00	HR
<b>5040</b>	51.4	7.05	37.3	7.73	50.0	40.0	48.80	39.00	CW
<b>5530</b>	56.4	14.7	27.0	15.12	55.0	30.0	53.50	28.70	HR
<b>5535</b>	56.4	12.1	32.3	13.18	55.0	35.0	53.80	34.00	HR
<b>5540</b>	56.4	9.6	37.3	11.03	55.0	40.0	53.80	39.00	HR
<b>5545</b>	56.4	7.1	42.3	8.58	55.0	45.0	53.80	44.00	HR
<b>6030</b>	61.4	17.3	26.8	18.82	60.0	30.0	58.30	28.50	HR
<b>6035</b>	61.4	14.7	32.0	16.93	60.0	35.0	58.50	33.70	HR
<b>6040</b>	61.4	12.1	37.3	14.67	60.0	40.0	58.80	39.00	HR
<b>6045</b>	61.4	9.6	42.3	12.21	60.0	45.0	58.80	44.00	HR
<b>6234</b>	63.6	16.3	31.1	18.98	62.2	34.2	60.60	32.80	HR
<b>6241</b>	63.6	12.3	39.1	15.51	62.2	41.8	61.00	40.80	HR
<b>6251</b>	63.6	7.4	48.9	10.20	62.2	51.6	61.00	50.60	HR
<b>6535</b>	66.4	17.4	31.7	20.99	65.0	35.0	63.30	33.40	HR
<b>6540</b>	66.4	14.7	37.0	18.74	65.0	40.0	63.50	38.70	HR
<b>6545</b>	66.4	12.1	42.3	16.15	65.0	45.0	63.80	44.00	HR
<b>6550</b>	66.4	9.6	47.3	13.39	65.0	50.0	63.80	49.00	HR
<b>7035</b>	71.4	20.0	31.5	25.31	70.0	35.0	68.00	33.20	HR
<b>7040</b>	71.4	17.4	36.7	23.13	70.0	40.0	68.30	38.40	HR
<b>7045</b>	71.4	14.7	42.0	20.56	70.0	45.0	68.50	43.70	HR
<b>7050</b>	71.4	12.1	47.2	17.70	70.0	50.0	68.80	48.90	HR
<b>7055</b>	71.4	9.6	52.3	14.57	70.0	55.0	68.80	54.00	HR
<b>7038</b>	71.6	18.3	35.0	24.05	70.2	38.4	68.40	36.70	HR
<b>7047</b>	71.6	13.8	44.0	19.67	70.2	46.9	68.80	45.70	HR
<b>7057</b>	71.6	8.4	54.8	13.09	70.2	57.6	69.00	56.50	HR
<b>7540</b>	76.4	20.0	36.4	27.82	75.0	40.0	73.00	38.10	HR
<b>7545</b>	76.4	17.4	41.7	25.27	75.0	45.0	73.30	43.40	HR
<b>7550</b>	76.4	14.7	47.0	22.37	75.0	50.0	73.50	48.70	HR
<b>7555</b>	76.4	12.1	52.2	19.19	75.0	55.0	73.80	53.90	HR
<b>7560</b>	76.4	9.6	57.2	15.81	75.0	60.0	73.80	58.90	HR

HR = Hot rolled  
CW = Cold worked

Type	Nom. delivery size			Weight kg/m	Guaranteed finished size, mm				
	OD mm	wall mm	ID mm		outer chocking OD	ID	inner chocking OD	ID	
<b>8040</b>	81.5	22.7	36.1	32.92	80.0	40.0	77.80	37.80	HR
<b>8045</b>	81.5	20.1	41.4	30.38	80.0	45.0	78.10	43.10	HR
<b>8050</b>	81.5	17.4	46.7	27.51	80.0	50.0	78.40	48.40	HR
<b>8055</b>	81.5	14.8	51.9	24.34	80.0	55.0	78.60	53.60	HR
<b>8060</b>	81.5	12.2	57.2	20.78	80.0	60.0	78.90	58.90	HR
<b>8065</b>	81.5	9.7	62.2	17.10	80.0	65.0	78.90	63.90	HR
<b>8447</b>	85.7	20.9	44.0	33.35	84.2	47.7	82.20	45.70	HR
<b>8452</b>	85.7	18.4	48.9	30.54	84.2	52.4	82.50	50.60	HR
<b>8545</b>	86.5	22.7	41.1	35.72	85.0	45.0	82.80	42.80	HR
<b>8550</b>	86.5	20.1	46.4	32.86	85.0	50.0	83.10	48.10	HR
<b>8555</b>	86.5	17.5	51.6	29.72	85.0	55.0	83.40	53.30	HR
<b>8560</b>	86.5	14.8	56.9	26.17	85.0	60.0	83.60	58.60	HR
<b>8565</b>	86.5	12.2	62.2	22.28	85.0	65.0	83.90	63.90	HR
<b>8570</b>	86.5	9.7	67.2	18.29	85.0	70.0	83.90	68.90	HR
<b>9050</b>	91.5	22.7	46.1	38.52	90.0	50.0	87.80	47.80	HR
<b>8952</b>	90.7	20.9	49.0	35.92	89.2	52.7	87.20	50.70	HR
<b>9055</b>	91.5	20.1	51.3	35.39	90.0	55.0	88.10	53.00	HR
<b>9060</b>	91.5	17.5	56.6	31.87	90.0	60.0	88.40	58.30	HR
<b>9065</b>	91.5	14.8	61.9	27.99	90.0	65.0	88.60	63.60	HR
<b>9070</b>	91.5	12.2	67.1	23.86	90.0	70.0	88.90	68.80	HR
<b>9075</b>	91.5	9.7	72.2	19.48	90.0	75.0	88.90	73.90	HR
<b>9550</b>	96.6	25.4	45.8	44.60	95.0	50.0	92.60	47.60	HR
<b>9555</b>	96.6	22.8	51.0	41.50	95.0	55.0	92.90	52.80	HR
<b>9560</b>	96.6	20.2	56.3	37.99	95.0	60.0	93.20	58.10	HR
<b>9565</b>	96.6	17.5	61.6	34.14	95.0	65.0	93.40	63.40	HR
<b>9570</b>	96.6	14.9	66.8	30.02	95.0	70.0	93.70	68.60	HR
<b>9575</b>	96.6	12.3	72.1	25.48	95.0	75.0	94.00	73.90	HR
<b>9580</b>	96.6	9.8	77.1	20.88	95.0	80.0	94.00	78.90	HR
<b>10050</b>	101.6	28.1	45.5	50.88	100.0	50.0	97.40	47.30	HR
<b>10055</b>	101.6	25.4	50.8	47.73	100.0	55.0	97.60	52.60	HR
<b>10060</b>	101.6	22.8	56.0	44.31	100.0	60.0	97.90	57.80	HR
<b>10065</b>	101.6	20.2	61.3	40.48	100.0	65.0	98.10	63.10	HR
<b>10070</b>	101.6	17.6	66.5	36.38	100.0	70.0	98.40	68.30	HR
<b>10075</b>	101.6	14.9	71.8	31.86	100.0	75.0	98.70	73.60	HR
<b>10080</b>	101.6	12.3	77.1	26.99	100.0	80.0	98.90	78.90	HR
<b>10085</b>	101.6	9.8	82.1	22.09	100.0	85.0	99.00	83.90	HR
<b>10555</b>	106.7	21.8	50.5	54.47	105.0	55.0	102.40	52.30	HR
<b>10560</b>	106.7	25.9	54.9	51.61	105.0	60.0	102.70	56.70	HR
<b>10565</b>	106.7	22.9	61.0	47.25	105.0	65.0	103.00	62.80	HR
<b>10570</b>	106.7	20.2	66.3	43.09	105.0	70.0	103.20	68.10	HR
<b>10575</b>	106.7	17.6	71.5	38.67	105.0	75.0	103.50	73.30	HR
<b>10580</b>	106.7	15.0	76.8	33.83	105.0	80.0	103.70	78.60	HR
<b>10585</b>	106.7	12.4	82.0	28.74	105.0	85.0	104.00	86.80	HR
<b>10590</b>	106.7	9.8	87.1	23.42	105.0	90.0	104.00	88.90	HR

Type	Nom. delivery size			Weight kg/m	Guaranteed finished size, mm				
	OD mm	wall mm	ID mm		outer chocking OD	ID	inner chocking OD	ID	
<b>11060</b>	111.7	28.2	55.4	58.00	110.0	60.0	107.40	57.20	HR
<b>11065</b>	111.7	25.5	60.7	54.21	110.0	65.0	107.70	62.50	HR
<b>11166</b>	112.7	25.4	61.9	54.69	111.0	66.2	108.70	63.70	HR
<b>11070</b>	111.7	22.9	66.0	50.07	110.0	70.0	107.90	67.80	HR
<b>11075</b>	111.7	20.3	71.2	45.67	110.0	75.0	108.20	73.00	HR
<b>11080</b>	111.7	17.6	76.5	40.84	110.0	80.0	108.45	78.30	HR
<b>11085</b>	111.7	15.0	81.8	35.67	110.0	85.0	108.70	83.60	HR
<b>11090</b>	111.7	12.4	87.0	30.26	110.0	90.0	109.00	88.80	HR
<b>11095</b>	111.7	9.8	92.1	24.63	110.0	95.0	109.00	94.00	HR
<b>11560</b>	116.7	30.8	55.1	65.25	115.0	60.0	112.10	56.90	HR
<b>11565</b>	116.7	28.2	60.4	61.47	115.0	65.0	112.40	62.20	HR
<b>11570</b>	116.7	25.5	65.7	57.35	115.0	70.0	112.60	67.50	HR
<b>11575</b>	116.7	22.9	70.9	52.97	115.0	75.0	112.90	72.70	HR
<b>11580</b>	116.7	20.3	76.2	48.17	115.0	80.0	113.20	78.00	HR
<b>11585</b>	116.7	17.6	81.5	43.01	115.0	85.0	113.40	83.30	HR
<b>11590</b>	116.7	15.0	86.7	37.62	115.0	90.0	113.70	88.50	HR
<b>11595</b>	116.7	12.4	92.0	31.78	115.0	95.0	113.90	93.90	HR
<b>11766</b>	118.8	28.5	61.9	63.39	117.0	66.5	114.40	63.70	HR
<b>11774</b>	118.8	24.5	69.9	56.89	117.0	74.1	114.80	71.70	HR
<b>11782</b>	118.8	20.0	78.9	48.63	117.0	82.7	115.30	80.70	HR
<b>12065</b>	121.8	30.9	60.1	69.20	120.0	65.0	117.20	61.90	HR
<b>12070</b>	121.8	28.2	65.4	65.09	120.0	70.0	117.40	67.20	HR
<b>12075</b>	121.8	25.6	70.6	60.73	120.0	75.0	117.70	72.40	HR
<b>12080</b>	121.8	23.0	75.9	55.95	120.0	80.0	118.00	77.70	HR
<b>12085</b>	121.8	20.3	81.2	50.81	120.0	85.0	118.20	83.00	HR
<b>12090</b>	121.8	17.7	86.4	45.44	120.0	90.0	118.50	88.20	HR
<b>12095</b>	121.8	15.1	91.7	39.62	120.0	95.0	118.70	93.60	HR
<b>120100</b>	121.8	12.4	97.0	33.45	120.0	100.0	119.00	98.90	HR
<b>12570</b>	126.8	30.9	65.1	73.00	125.0	70.0	122.20	66.90	HR
<b>12575</b>	126.8	28.2	70.4	68.57	125.0	75.0	122.40	72.20	HR
<b>12580</b>	126.8	25.6	75.6	63.89	125.0	80.0	122.70	77.40	HR
<b>12585</b>	126.8	23.0	80.9	58.78	125.0	85.0	123.00	82.70	HR
<b>12590</b>	126.8	20.4	86.1	53.42	125.0	90.0	123.20	88.00	HR
<b>12595</b>	126.8	17.7	91.4	47.62	125.0	95.0	123.50	93.30	HR
<b>1</b>									